

§ 11.32

47 CFR Ch. I (10–1–14 Edition)

(f) The State, Territory and Offshore (Marine Area) ANSI number codes (SS) are as follows. County ANSI numbers (CCC) are contained in the State EAS Mapbook.

	ANSI No.
State:	
AL	01
AK	02
AZ	04
AR	05
CA	06
CO	08
CT	09
DE	10
DC	11
FL	12
GA	13
HI	15
ID	16
IL	17
IN	18
IA	19
KS	20
KY	21
LA	22
ME	23
MD	24
MA	25
MI	26
MN	27
MS	28
MO	29
MT	30
NE	31
NV	32
NH	33
NJ	34
NM	35
NY	36
NC	37
ND	38
OH	39
OK	40
OR	41
PA	42
RI	44
SC	45
SD	46
TN	47
TX	48
UT	49
VT	50
VA	51
WA	53
WV	54
WI	55
WY	56
Terr.:	
AS	60
FM	64
GU	66
MH	68
PR	72
PW	70
UM	74
VI	78
Offshore (Marine Areas) ¹ :	
Eastern North Pacific Ocean, and along U.S. West Coast from Canadian border to Mexican border	57

	ANSI No.
North Pacific Ocean near Alaska, and along Alaska coastline, including the Bering Sea and the Gulf of Alaska	58
Central Pacific Ocean, including Hawaiian waters	59
South Central Pacific Ocean, including American Samoa waters	61
Western Pacific Ocean, including Mariana Island waters	65
Western North Atlantic Ocean, and along U.S. East Coast, from Canadian border south to Currituck Beach Light, N.C.	73
Western North Atlantic Ocean, and along U.S. East Coast, south of Currituck Beach Light, N.C., following the coastline into Gulf of Mexico to Bonita Beach, FL., including the Caribbean	75
Gulf of Mexico, and along the U.S. Gulf Coast from the Mexican border to Bonita Beach, FL	77
Lake Superior	91
Lake Michigan	92
Lake Huron	93
Lake St. Clair	94
Lake Erie	96
Lake Ontario	97
St. Lawrence River above St. Regis	98

¹ Effective May 16, 2002, analog radio and television broadcast stations, analog cable systems and wireless cable systems may upgrade their existing EAS equipment to add these marine area location codes on a voluntary basis until the equipment is replaced. All models of EAS equipment manufactured after August 1, 2003, must be capable of receiving and transmitting these marine area location codes. EAS Participants that install or replace their EAS equipment after February 1, 2004, must install equipment that is capable of receiving and transmitting these location codes.

[59 FR 67092, Dec. 28, 1994, as amended at 60 FR 55999, Nov. 6, 1995; 61 FR 54952, Oct. 23, 1996; 63 FR 29663, June 1, 1998; 67 FR 18508, Apr. 16, 2002; 67 FR 77174, Dec. 17, 2002; 69 FR 72031, Dec. 10, 2004; 70 FR 71033, Nov. 25, 2005; 77 FR 16701, Mar. 22, 2012]

§ 11.32 EAS Encoder.

(a) EAS Encoders must at a minimum be capable of encoding the EAS protocol described in §11.31 and providing the EAS code transmission requirements described in §11.51. EAS encoders must additionally provide the following minimum specifications:

(1) *Encoder programming.* Access to encoder programming shall be protected by a lock or other security measures and be configured so that authorized personnel can readily select and program the EAS Encoder with Originator, Event and Location codes for either manual or automatic operation.

(2) *Inputs.* The encoder shall have at least one input port used for audio

messages and at least one input port used for data messages.

(3) *Outputs.* The encoder shall have at least one audio output port and at least one data output port.

(4) *Calibration.* EAS Encoders must provide a means to comply with the modulation levels required in §11.51(f).

(5) *Day-Hour-Minute and Identification Stamps.* The encoder shall affix the JJJHHMM and LLLLLLLL codes automatically to all initial messages.

(6) *Program Data Retention.* Program data and codes shall be retained even with the power removed.

(7) *Indicator.* An aural or visible means that it activated when the Preamble is sent and deactivated at the End of Message code.

(8) *Spurious Response.* All frequency components outside 200 to 4000 Hz shall be attenuated by 40 dB or more with respect to the output levels of the mark or space frequencies.

(9) *Attention Signal generator.* The encoder must provide an attention signal that complies with the following:

(i) *Tone Frequencies.* The audio tones shall have fundamental frequencies of 853 and 960 Hz and not vary over ± 0.5 Hz.

(ii) *Harmonic Distortion.* The total harmonic distortion of each of the audio tones may not exceed 5% at the encoder output terminals.

(iii) *Minimum Level of Output.* The encoder shall have an output level capability of at least +8 dBm into a 600 Ohm load impedance at each audio tone. A means shall be provided to permit individual activation of the two tones for calibration of associated systems.

(iv) *Time Period for Transmission of Tones.* The encoder shall have timing circuitry that automatically generates the two tones simultaneously for a time period of 8 seconds.

(v) *Inadvertent activation.* The switch used for initiating the automatic generation of the simultaneous tones shall be protected to prevent accidental operation.

(vi) *Indicator Display.* The encoder shall be provided with a visual and/or aural indicator which clearly shows that the Attention Signal is activated.

(b) *Operating Temperature and Humidity.* Encoders shall have the ability to

operate with the above specifications within an ambient temperature range of 0 to +50 degrees C and a range of relative humidity of up to 95%.

(c) *Primary Supply Voltage Variation.* Encoders shall be capable of complying with the requirements of this section during a variation in primary supply voltage of 85 percent to 115 percent of its rated value.

(d) *Testing Encoder Units.* Encoders not covered by §11.34(e) of this part shall be tested in a 10 V/m minimum RF field at an AM broadcast frequency and a 0.5 V/m minimum RF field at an FM or TV broadcast frequency to simulate actual working conditions.

[59 FR 67092, Dec. 28, 1994, as amended at 77 FR 16703, Mar. 22, 2012]

§ 11.33 EAS Decoder.

(a) An EAS Decoder must at a minimum be capable of providing the EAS monitoring functions described in §11.52, decoding EAS messages formatted in accordance with the EAS Protocol described in §11.31, and converting Common Alerting Protocol (CAP)-formatted EAS messages into EAS alert messages that comply with the EAS Protocol, in accordance with §11.56(a)(2), with the exception that the CAP-related monitoring and conversion requirements set forth in §§11.52(d)(2) and 11.56(a)(2) can be satisfied via an Intermediary Device, as specified in §11.56(b), provided that all other requirements set forth in this part are met. An EAS Decoder also must be capable of the following minimum specifications:

(1) *Inputs.* Decoders must have the capability to receive at least two audio inputs from EAS monitoring assignments, and at least one data input. The data input(s) may be used to monitor other communications modes such as Radio Broadcast Data System (RBDS), NWR, satellite, public switched telephone network, or any other source that uses the EAS protocol.

(2) *Valid codes.* There must be a means to determine if valid EAS header codes are received and to determine if preselected header codes are received.

(3) *Storage.* Decoders must provide the means to: